


MIRROR-ROCK

6 Flute 55° Helix Endmill with Corner Radius

EMR 610



Technical Info. Page No. **144**

Steels	Stainless Steels	Cast Irons	Hardened Steels <65HRC	Titaniums	Super Alloys	Aluminiums
-	-	-	-	-	-	-

d ₁	d ₁	d ₂	d ₃	l ₂	l ₃	l ₁	r	z	EDP No. HA	EDP No. HA
	tol.	h6	-0.1	±0.50	±0.50	±0.80	±0.015		ALD	DX
6.0	-0.025	6	5.8	13.0	21	57	0.50	6	EMRD 6100M 0600 050	EMRX 6100M 0600 050
8.0	-0.025	8	7.6	19.0	27	63	0.50	6	EMRD 6100M 0800 050	EMRX 6100M 0800 050
10.0	-0.035	10	9.5	22.0	32	72	0.50	6	EMRD 6100M 1000 050	EMRX 6100M 1000 050
12.0	-0.035	12	11.5	26.0	38	83	0.50	6	EMRD 6100M 1200 050	EMRX 6100M 1200 050
16.0	-0.035	16	15.5	32.0	44	92	1.00	6	EMRD 6100M 1600 100	EMRX 6100M 1600 100
20.0	-0.035	20	19.5	38.0	54	104	1.00	6	EMRD 6100M 2000 100	EMRX 6100M 2000 100

HB Weldon Shank available on request. Order Code for ALD Coated : EMRD 6101 | Order Code for DX Coated: EMRX 6101

STEELS

INOX

SUPERNOX

CHIPSPLITTERS

Aluminiums

ROCKSTARS

MICRO MILLS

UNIVERSAL

DRILLS

MATERIAL		Hardness	ap max xD	ae max xD	Vc (m/min)	fz (mm/z) Ø										
COPY MILLING [EMBD 2100]						1	2	3	4	5	6	8	10	12	16	20
P	High tensile strength steel	35-45 HRC	0.05	0.2	140-180	0.009	0.012	0.018	0.025	0.032	0.038	0.048	0.057	0.067	0.095	0.108
H	Hardened steel	45-55HRC	0.05	0.2	80-100	0.007	0.010	0.014	0.020	0.026	0.030	0.038	0.045	0.054	0.076	0.086
SLOTTING [EMSD 2100]																
P	High tensile strength steel	35-45 HRC	0.2	1	30-70	0.005	0.008	0.012	0.016	0.020	0.026	0.031	0.037	0.044	0.058	0.075
H	Hardened steel	45-55HRC	0.1	1	20-40	0.004	0.007	0.010	0.014	0.018	0.023	0.027	0.032	0.039	0.051	0.065
SIDE MILLING [EMSD 4100]																
P	High tensile strength steel	35-45 HRC	1	0.05	40-60	0.007	0.014	0.020	0.027	0.031	0.034	0.044	0.057	0.068	0.088	0.112
H	Hardened steel	45-55HRC	1	0.05	20-40	0.006	0.012	0.018	0.024	0.027	0.030	0.039	0.050	0.060	0.077	0.098
SIDE MILLING																
P	High tensile strength steel	35-45 HRC	1.5	0.05	20-60		0.012	0.017	0.023	0.026	0.029	0.038	0.048	0.058	0.075	0.095
H	Hardened steel	45-55HRC	1.5	0.05	20-40		0.010	0.015	0.020	0.023	0.025	0.033	0.042	0.051	0.065	0.083
SIDE MILLING																
P	High tensile strength steel	35-45 HRC	1.5	0.02	60-100			0.007	0.010	0.012	0.014	0.022	0.027	0.033	0.045	0.058
H	Hardened steel	45-55HRC	1.5	0.02	50-70			0.006	0.008	0.010	0.013	0.019	0.024	0.029	0.039	0.051
SLOTTING																
P	High tensile strength steel	35-45 HRC	0.3	1	30-50			0.008	0.011	0.013	0.015	0.020	0.024	0.028	0.034	0.042
H	Hardened steel	45-55HRC	0.2	1	20-40			0.007	0.010	0.012	0.014	0.019	0.022	0.026	0.032	0.039
SIDE MILLING																
P	High tensile strength steel	35-45 HRC	1.2	0.2	40-60			0.010	0.014	0.017	0.020	0.026	0.031	0.035	0.044	0.054
H	Hardened steel	45-55HRC	1	0.1	30-50			0.014	0.019	0.023	0.027	0.035	0.042	0.048	0.061	0.074
HELICAL MILLING																
P	High tensile strength steel	35-45 HRC	3°	0.4	30-50			0.006	0.008	0.011	0.012	0.016	0.019	0.022	0.028	0.034
H	Hardened steel	45-55HRC	2°	0.4	20-40			0.007	0.009	0.011	0.013	0.017	0.020	0.023	0.029	0.035
TROCHOIDAL MILLING																
P	High tensile strength steel	35-45 HRC	1	0.1	50-70			0.021	0.029	0.034	0.041	0.054	0.064	0.073	0.092	0.112
H	Hardened steel	45-55HRC	1	0.1	40-60			0.029	0.040	0.048	0.057	0.074	0.088	0.101	0.126	0.154

Technical Data provided should be considered advisory only as variations may be necessary depending on the particular application